



<b>Model</b>	<b>DMD-91208</b>
<b>Compression Format</b>	H.264
<b>Video System</b>	NTSC / PAL
<b>Video Input/Output</b>	BNC 8CH In/ 1CH Out, VGA 1CH Out
<b>Audio Input/Output</b>	RCA 8CH In/ 1CH Out
<b>Alarm Input/Output</b>	Alarm 4CH In/ 1CH Out
<b>Preview resolution</b>	720 x 480 ( NTSC ), 704 x 576 ( PAL ) ; Playback resolution: CIF x 8 / D1 x 1
<b>Real time recording support</b>	CIF:352x240 with 240 Fps (NTSC); 352x288 with 200 Fps (PAL) D1:720x480 with 60 Fps (NTSC); 704x576 with 50 Fps (PAL)
<b>Video Compression Rate</b>	CIF Resolution, 3 grade available
<b>Audio Compression</b>	8kHz*16bit, ADPCM
<b>Motion Detection</b>	PAL 13*10 (130) ; NTSC 13*8 (104) 4 grade available
<b>Communication Interface</b>	1pc RJ45 10M/100M Ethernet, 1pc port, 1pc RS485 port
<b>Hard Disk</b>	2 SATA Hard Disc interface
<b>USB port</b>	2pc (Mouse port and USB2.0 port)
<b>Network Protocol</b>	TCP/IP、PPPOE、DDNS and NTP
<b>VGA port</b>	1pc(optional) Resolution:800x600, 1024x768
<b>Special Feature</b>	Support GPRS/CDMA/EDGE/3G mobile phone view
<b>Power Supply</b>	12V/3A
<b>Working Temperature</b>	0℃--+55℃
<b>Working Humidity</b>	10%--90%
<b>Dimension</b>	L382 x W258 x H60mm
<b>Package</b>	52*48*45 5PCS 18.3KG
<b>Weight</b>	4Kg