





ISSUE NO.:

DIRECTION OF ROTATION



CONFIRMED & ACCEPTED BY CUSTOMER (客户接受&确认)
COMPANY, CHOP & SIGNATURE (盖章&签名)

MODEL NO.

HS-540SA-7120

DES'D

SAMPLE MO.

A081205-1A

CHK'D

APP'D

SCALE

1:1



MOTOR OUTGOING SPECIFICATION

Model No. : HS-540SA-7120

Sample No. : A081205-1A

1.Motor Type: 马达类型

Small PMDC motor
微型直流马达

2.Standard Operating Conditions: 标准工作条件

- 2-1 Rated Voltage(额定电压): 7.0V DC CONSTANT between motor terminals(端子电压7.0V)
2-1 Direction of Rotation(旋转方向): CCW, when viewed from output shaft side(从输出轴端看CCW)

3.Electrical Characteristics(at initial stage after 30 seconds run-in): 电气特性(起动30秒后初始阶段)

- 3-1 No Load Current(空载电流): 1.80A max
3-2 No Load Speed(空载转速): 20400±12%rpm
3-3 Rated Load(tested with fan 40*15mm): 81.64g.cm
额定负载(40*15mm风叶)
3-4 Rated Current(额定电流): 4.70A max
3-5 Rated Speed(额定转速): 19500±10%rpm
3-6 Noise(噪音): 30cm≤70dB
3-7 Motor Characteristic Curve(马达特性曲线): See Motor Performance Curves And Characteristics(看马达特性曲线图).

4.Mechanical Characteristics: 机械特性

- 4-1 External Apperance(外形): See Outline(看外形图)
4-2 End Play(虚位): 0.05~0.5mm
4-3 Runout of Shaft Extension(轴突端跳动): 0.02mm max

CONFIRMED & ACCEPTED BY CUSTOMER (客户接受&确认)

COMPANY,CHOP & SIGNATURE (盖章&签名)


PREPARED: _____ CHECKED: _____ APPROVED: _____

MODEL (型号): HS-540SA-7120

CONSTANT (转向): CCW F/Y

VOLTAGE (电压): 7.0V/DC

DATE (时间): 2008/12/05



At No Load (空载)

SPEED (转速): 20400 RPM

CURRENT (电流): 1.59 AMP

At stall (Extrapolated) (失速)

TORQUE (力矩): 1850.56 G.CM

CURRENT (电流): 58.5 AMP

At maximum efficiency (最大效率)

EFFICIENCY (效率): 69.7 %

TORQUE (力矩): 261.9 G.CM

SPEED (转速): 17512 RPM

CURRENT (电流): 9.64 AMP

OUTPUT (功率): 47.12 WATTS

At maximum power (最大功率)

TORQUE (力矩): 925.3 G.CM

SPEED (转速): 10200 RPM

CURRENT (电流): 30.04 AMP

OUTPUT (功率): 96.96 WATTS

THE CURVES REPRESENT THE THEORENICAL PERFORMANCE OF THE SAMPLE ONLY.
曲线值表示样品的技术特性

PREPARED: _____

CHECKED: _____

APPROVED: _____