

Piezo Siren

Piezo siren



LD-80



LD-80

Flush mount siren



LD-A93



LD-105



LD-97



LD-98

Piezo siren with strobe



LD-A92



LD-96



LD-96



LD-H96



LD-H96



LD-87

Model No.	LD-80	LD-A93	LD-105	LD-97	LD-98	LD-A92	LD-96	LD-H96	LD-87
Operating voltage(VDC)	7~14	10~14	7~14	10~14	7~14	10~14	10~14	10~14	10~14
Current consumption(mA)	130	130	130	130	150	250	250	250	250
Operating frequency(KHz)	1.5~3.5	2.4~3.7	2.4~3.7	2.4~3.7	2.4~3.7	2.4~3.7	2.4~3.7	2.4~3.7	2.4~3.7
Alarm output(dB)	110	110	110	110	110	110	110	110	122
Reverse polarity protection	V	V	V	V	V	V	V	V	V
Weight(grom)	47	110	100	120	100	110	120	120	160

Intruder alarm with strobe



LD-281 (Negative activated)

LD-282 (Positive activated)

LD-283 (W/Back-up battery positive activated)

LD-285 (W/Back-up battery negative activated)

Specification:

- ◆ Operating voltage: 11V~14V DC (12V Nominal)
- ◆ Power consumption: Siren: 200mA
Strobe: 250mA
- ◆ Siren output: 115 decibel
- ◆ Strobe luminous flux: 25lm
- ◆ Size(mm): 241(L)x160(W)x51(H)

Features:

- ◆ Built-in Anti-tamper switch/with Feed-back Terminal
- ◆ Weatherproof, UV proof, Hi-impact. (3mm Polycarbonate housing)
- ◆ Six strobe lights polarity reverse protection
- ◆ Cable-cutting/Movement Activated(LD-283/LD-285)
- ◆ Circuit for AUTO-RECHARGING battery(LD-283/LD-285)